



A Green Solutions Company™

EZ Ball Valve Coupling Connector

EZ-FLO CBV Connection

Ball valve coupling (CBV) connectors are available in sizes 3/4" through 4" with socket x socket connections. They are PVC schedule 40 with 1/4" stainless steel barbed tubing connectors. They are used to connect the EZ-FLO systems to the irrigation flow line with the 1/4" flexible tubing, provided with the EZ-FLO systems. They provide the ability to adjust the differential pressure between the inlet and outlet connection to the irrigation system flow line.



EZ-FLO CBVT Connection

Ball valve coupling threaded (CBVT) connectors are available in sizes 3/4" through 1.25" with FIPTx FIPT connections. They are PVC schedule 40 with 1/4" stainless steel barbed tubing connectors. They are used to connect the EZ-FLO systems to the irrigation flow line with the 1/4" flexible tubing, provided with the EZ-FLO systems. They provide the ability to adjust the differential pressure between the inlet and outlet connection to the irrigation system flow line.



Part Number	Size	A	B
CBV-075	3/4" SOC	7"	1"
CBV-100	1" SOC	8"	1 1/4"
CBV-125	1 1/4" SOC	9 1/4"	1 1/4"
CBV-150	1 1/2" SOC	10 3/4"	1 1/4"
CBV-200	2" SOC	12 1/2"	1 3/4"
CBV-250	2 1/2" SOC	13"	1 3/4"
CBV-300	3" SOC	16 1/2"	1 3/4"
CBV-400	4" SOC	18 1/2"	2"
CBVT-075	3/4" THD	7"	1"
CBVT-100	1" THD	8"	1 1/4"
CBVT-125	1 1/4" THD	9 1/2"	1 1/4"

